

| Specifications | 125mm Range | 150mm Range | 190mm Range |
|---|---|---|---|
| Board Size (W x L) | 125mm x 1860-2060mm | 150mm x 1860-2060mm | 190mm x 1860-2060mm |
| Thickness | 14mm | 14mm | 14mm |
| Pack Size | 1.86-2.06m ² | 1.674-1.71m ² | 2.121-2.166m ² |
| Finish | Smooth UV Lacquer | Smooth UV Lacquer | Smooth UV Lacquer |
| Grade & Colour Variation | "Standard & Better" High Colour Variations | "Standard & Better" High Colour Variations | "Standard & Better" High Colour Variations |
| Profile | Tongue & Groove | Tongue & Groove | Tongue & Groove |
| Stability/Density | Varies | Varies | Varies |
| Construction | Multi-Layer Ply Core 3mm Timber | Multi-Layer Ply Core 1.2mm Timber | Multi-Layer Ply Core 3mm Timber |
| Raft Size (W x L) | 8m x 12m | 8m x 12m | 8m x 12m |
| Installation Method | Floating or Direct Stick | Floating or Direct Stick | Floating or Direct Stick |
| Perimeter Gap & Coverage - min | 10-15mm | 10-15mm | 10-15mm |
| Floor Level over 2m | 2mm | 2mm | 2mm |
| Moisture Protection | 8 hours | 8 hours | 8 hours |
| Direct UV and Heat Protection | Standard 2 Hours | Standard 2 Hours | Standard 2 Hours |
| Under Floor Heating | Yes | Yes | Yes |
| Climate & Environment Control | High | High | High |
| Wear Resistance | High Residential 11 Layers UV Coating | High Residential 11 Layers UV Coating | High Residential 11 Layers UV Coating |
| Scratch Resistance | Standard | Standard | Standard |
| Certifications* | | | |
| Fire Safe | Yes | Yes | Yes |
| Slip Rated | P2 | P2 | P2 |
| Emission Compliant | E1 | E1 | E1 |
| Acoustic Compliant | Yes | Yes | Yes |
| Residential Warranty* | 30 years | 30 years | 30 years |
| Medium Commercial Warranty* | 5 years | 5 years | 5 years |

* The information and data presented is believed to be accurate and has been compiled from sources believed to be reliable at the time of preparation. Full warranty terms and conditions and product guidelines are available for download on the Clever Choice Website www.cleverchoice.com.au.