## **AWTA PRODUCT TESTING**

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

2000kg/m3

Test Number:

Issue Date

**Print Date** 

23-001585

23/05/2023

23/05/2023

Client: Paxwood Pty Ltd T/A Clever Choice Design Floors

Unit 1

164 Adderlely Street

West Auburn NSW 2144

Sample Description Clients Ref : "Clever Vinyl 2.5mm"

Vinyl Flooring Planks
Colour: Timber look
End Use: Flooring

Nominal Composition: Virgin PVC

Nominal Mass per Unit Area/Density:

Nominal Thickness: 2.5



295529 64191 Page 1 of 2

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.





## AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client: Paxwood Pty Ltd T/A Clever Choice Design Floors

Unit 1

164 Adderlely Street

West Auburn NSW 2144

Test Number : 23-001585 Issue Date : 23/05/2023

Print Date : 23/05/2023

AS 4586-2013 Appendix A Slip Resistance Classification of new Pedestrian Surface Materials

Wet Pendulum Test Method

Date of Testing 18-05-2023
Operator AWTA Test Operator 4

Test Temperature (20±5degC) 22 °C

Sample Preparation Sample washed with pH neutral detergent the

dried

Test Direction Length
Fixed/Unfixed Unfixed

Slider No 96 Batch No 15

 Length
 1
 2
 3
 4
 5
 SRV

 British Pendulum
 30
 30
 31
 29
 30
 30

number

Classification P2

Equipment: Cooper Pendulum Skid Tester Serial No: 1433-01 Calibrated 21/09/2021 Slider prepared using P400 and 3µm lapping film.

These results apply only to the specimens tested and it is recommended that before selection of flooring or paving materials the effect of service conditions, including maintenance and wear on their slip resistance be checked.

295529 64191 Page 2 of 2

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



MICHAEL A. JACKSON B.Sc.(Hons)

Fiona McDonald

APPROVED SIGNATORY